

RSSI Interpretation and Timing

By Siri Namtvedt

Keywords

- CC1100
- CC1101
- CC1110
- CC1111
- CC2500
- CC2510
- CC2511
- RSSI

1 Introduction

The Received Signal Strength Indicator is a measure of the RF power input to the transceiver. The RSSI value is based on the gain setting in the RX chain and the measured signal level in the channel. In RX mode, the RSSI value can be read continuously from the `RSSI` status register

until the demodulator detects a sync word (when sync word detection is enabled). At that point the RSSI readout value is frozen until the next time the chip enters the RX state. If sync word detection is disabled, the `RSSI` register will be continuously updated.

Table of Contents

KEYWORDS	1
1 INTRODUCTION	1
2 ABBREVIATIONS	2
3 RSSI REGISTER INTERPRETATION	3
4 RSSI OFFSET	3
5 RSSI UPDATE RATE	3
6 IMPROVING RSSI READOUT ACCURACY	8
7 RSSI THRESHOLD	8
8 REFERENCES	9
9 GENERAL INFORMATION	10
9.1 DOCUMENT HISTORY	10

2 Abbreviations

AGC	Automatic Gain Control
BW	Band Width
CS	Carrier Sense
RSSI	Received Signal Strength Indicator
WOR	Wake on Radio

3 RSSI Register Interpretation

The RSSI value read from the `RSSI` status register is a 2's complement number and is in dBm with $\frac{1}{2}$ dB resolution. The following procedure can be used to convert the RSSI reading to an absolute power level (`RSSI_dBm`).

Assume that the RSSI offset is 72 dB and that `11111010b` is read from the `RSSI` register.

If `11111010b` is interpreted as a 2's complement number it has the value -6.

This means that the RSSI value, before taking the offset into account, is -3 dBm. Subtracting the RSSI offset, the RSSI value in dBm ends up at -3 dBm - 72 dB = -75 dBm.

```

UINT8 rssi_dec;
INT16 rssi_dBm;
UINT8 rssi_offset = 72;

rssi_dec = halSpiReadStatus(CCxxx0_RSSI);

if (rssi_dec >= 128)
    rssi_dBm = (INT16)((INT16)( rssi_dec - 256) / 2) - rssi_offset;
else
    rssi_dBm = (rssi_dec / 2) - rssi_offset;

```

4 RSSI Offset

The RSSI offset will vary with register settings, and hence different data rates (using different AGC settings) will have different RSSI offset. Table 1 shows the RSSI offset for some data rates for CC1100, CC1101, CC1110/CC1111, CC2500, and CC2510/CC2511.

Data Rate [kBaud]	CC1100		CC1101		CC1110/ CC1111			CC2500	CC2510/ CC2511
	RSSI Offset [dB]		RSSI Offset [dB]		RSSI Offset [dB]			RSSI Offset [dB]	RSSI Offset [dB]
	433 [MHz]	868 [MHz]	433 [MHz]	868 [MHz]	315 [MHz]	433 [MHz]	868 [MHz]		
1.2	75	74	74	74	74	75	73	-	-
2.4	-	-	-	-	-	-	-	71	74
10	-	-	-	-	-	-	-	69	74
38.4	75	74	74	74	73	74	73	-	-
250	79	78	74	74	74	73	77	72	71
500	79	77	74	74	-	-	-	72	72

Table 1. RSSI Offset

When using data rates other than the ones in Table 1, it is possible to find the RSSI offset by applying a known input power and then read out the RSSI value.

5 RSSI Update Rate

The RSSI update rate, f_{RSSI} (Equation 1), depends on the receiver filter bandwidth ($BW_{channel}$, Equation 2) and filter length (see the `AGCCTRL0` register in the data sheet ([1], [2], [3], [7], and [8])).

$$f_{RSSI} = \frac{2 \cdot BW_{channel}}{8 \cdot 2^{FILTER_LENGTH}}$$

Equation 1. RSSI Update Rate

$$BW_{channel} = \frac{f_{xosc}}{8 \cdot (4 + CHANBW_M) \cdot 2^{CHANBW_E}}$$

Equation 2. Receiver Filter Bandwidth

The time it takes from the chip is in RX mode to a valid RSSI value is present in the `RSSI` register can be estimated as shown in Equation 3 (only valid for weak signals; ~-70 dBm or lower):

$$RSSI \text{ Response Time} = \frac{8}{BW_{channel}} \cdot \left(\frac{WAIT_TIME}{2} + 1 + 2^{FILTER_LENGTH} \right) + MAX \left[\frac{20}{BW_{channel}}, \frac{10}{(8 \cdot DataRate)} \right]$$

Equation 3. RSSI Response Time

It is important to notice that this equation only gives an indication of the time required in RX before a valid RSSI value can be obtained (and it is only valid for weak signals). Adding a safety margin is therefore necessary in a real life application.

Example (CC2500):

Data Rate = 10 kBaud
`AGCCTRL0 = 0x91` \Rightarrow `AGCCTRL0.WAIT_TIME = 1`
`AGCCTRL0.FILTER_LENGTH = 1`
`MDMCFG4 = 0x78` \Rightarrow `MDMCFG4.CHANBW_M = 3`
`MDMCFG4.CHANBW_E = 1`

$$BW_{channel} = \frac{f_{xosc}}{8 \cdot (4 + CHANBW_M) \cdot 2^{CHANBW_E}} = \frac{26 \cdot 10^6}{8 \cdot (4 + 3) \cdot 2^1} = \frac{26 \cdot 10^6}{112} = 232142.9 [Hz]$$

$$RSSI \text{ Response Time} = \frac{8}{232142.9} \cdot \left(\frac{1}{2} + 1 + 2^1 \right) + MAX \left[\frac{20}{232142.9}, \frac{10}{(8 \cdot 10000)} \right] = 246 [\mu s]$$

The equation for estimating the RSSI response time can for example be used when estimating the time the radio will be in RX when using WOR and direct RX termination based on RSSI measurements (`MCSM2.RX_TIME_RSSI = 1`). Using this feature, RX mode will be terminated if the RSSI level is below a programmable threshold. For the CC1100, the following test where done:

A CC1100, operating at 76.8 kBaud and $BW_{channel} = 232$ kHz, was put in WOR mode with direct RX termination (This test cannot be performed on CC1110/CC1111 and CC2510/CC2511 since these devices do not support WOR). For different values of `AGCCTRL0.WAIT_TIME` and `AGCCTRL0.FILTER_LENGTH`, the time spent in RX (before terminating due to no CS) was measured and compared to the estimated RSSI response time. The results can be seen in Table 2.

FILTER_LENGTH	WAIT_TIME	Estimated RSSI Response Time [us]	Measured time spent in RX before termination [us]
0	0	155	152
0	1	172	170
0	2	190	186
0	3	207	204
1	0	190	189
1	1	207	204
1	2	224	222
1	3	241	238
2	0	258	257
2	1	276	276
2	2	293	294
2	3	310	316

Table 2. Estimated vs. Measured RSSI Response Time (76.8 kBaud)

For stronger signals, it will take longer time before one can read a valid RSSI value since the AGC requires longer time to set the gain. Assume an application where one wants to put the radio in RX for a minimum amount of time before reading the `RSSI` register. One of the challenges is that the time taken before a valid RSSI value can be read varies with signal strength, and the signal strength is unknown. In this case one should do a set of measurements where a known strong signal is input to the receiver, and the `RSSI` register is read continuously. One should then measure the time from the radio enters RX state until a valid RSSI value is available. Figure 1, Figure 2, and Figure 3 shows 3 different signals strengths (-50 dBm, -70 dBm, and -86 dBm) at 3 different data rates (2.4 kBaud, 10 kBaud, and 250 kBaud) and the time it takes before a valid value can be read from the `RSSI` register. CC2500 was used for this test and register settings were obtained from SmartRF® Studio.

Pseudo code for test firmware:

1. Strobe RX
2. Wait until the radio is in RX mode
3. Start reading the `RSSI` register repeatedly and store the values in a buffer (for the plots in Figure 1, Figure 2, and Figure 3, the `RSSI` register was read 250 times, with 5.96 us between readings)
4. From the `RSSI` register values, calculate the actual RSSI value and plot the RSSI values vs. time




Figure 1. RSSI Value vs. Time (2.4 kBaud)

$$RSSI \text{ Response Time} = \frac{8}{203125} \cdot \left(\frac{1}{2} + 1 + 2^1 \right) + \text{MAX} \left[\frac{20}{203125}, \frac{10}{(8 \cdot 2400)} \right] = 658.7 \text{ [us]}$$





Figure 2. RSSI Value vs. Time (10 kBaud)

$$RSSI \text{ Response Time} = \frac{8}{232142.857} \cdot \left(\frac{1}{2} + 1 + 2^1 \right) + \text{MAX} \left[\frac{20}{232142.857}, \frac{10}{(8 \cdot 10000)} \right] = 245.6 \text{ [us]}$$



$$RSSI \text{ Response Time} = \frac{8}{541666.667} \cdot \left(\frac{3}{2} + 1 + 2^1 \right) + MAX \left[\frac{20}{541666.667}, \frac{10}{(8 \cdot 250000)} \right] = 103.4 [us]$$

6 Improving RSSI Readout Accuracy

It is important to be aware that in a real system, the output power from the transmitter and variations in the transmission path will contribute to the RSSI inaccuracy. However, there are certain steps one can do, to improve the RSSI readout accuracy

- 1) Calculate an average RSSI value based on several readouts
- 2) Follow workaround for the SPI read synchronization issue (see [4], [5], and [6]). This is only necessary on the CC1100/CC1101/CC2500, not the SoCs.

7 RSSI Threshold

Table 3 shows typical RSSI value at CS threshold when the data rate is 250 kBaud, AGCCTRL2.MAGN_TARGET = 3, and AGCCTRL1.CARRIER_SENSE_ABS_THR = 0.

		AGCCTRL2.MAX_DVGA_GAIN[1:0]			
		00	01	10	11
AGCCTRL2.MAX_LNA_GAIN[2:0]	000	-96	-90	-84	-78.5
	001	-94.5	-89	-83	-77.5
	010	-92.5	-87	-81	-75
	011	-91	-85	-78.5	-73
	100	-87.5	-82	-76	-70
	101	-85	-79.5	-73.5	-67.5
	110	-83	-76.5	-70.5	-65
	111	-78	-72	-66	-60

Table 3. Typical RSSI Value in dBm at CS Threshold

Assume MAX_LNA_GAIN = 4 and MAX_DVGA_GAIN = 1. This means that when MAGN_TARGET = 3 and CARRIER_SENSE_ABS_THR = 0, the RSSI value at CS threshold is -82 dBm.

AGCCTRL2.MAGN_TARGET[2:0]		AGCCTRL1.CARRIER_SENSE_ABS_THR[3:0]	
0	24 dBm	-8	Absolute carrier sense threshold disabled
1	27 dBm	-7	7 dB below MAGN_TARGET setting
2	30 dBm
3	33 dBm	-1	1 dB below MAGN_TARGET setting
4	36 dBm	0	At MAGN_TARGET setting
5	38 dBm	1	1 dB above MAGN_TARGET setting
6	40 dBm
7	42 dBm	7	7 dB above MAGN_TARGET setting

Table 4. MAGN_TARGET and CARRIER_SENSE_ABS_THR Settings

Changing MAGN_TARGET to 7 and CARRIER_SENSE_ABS_THR to 4, will change the CS threshold from -82 dBm to -69 dBm $(-82 + (42 - 33) + (4 - 0) = -69 \text{ [dBm]})$.

8 References

- [1] CC1100 Single-Chip Low Cost Low Power RF-Transceiver, Data sheet ([cc1100.pdf](#))
- [2] CC1101 Single-Chip Low Cost Low Power RF-Transceiver, Data sheet ([cc1101.pdf](#))
- [3] CC2500 Single-Chip Low Cost Low Power RF-Transceiver, Data sheet ([cc2500.pdf](#))
- [4] CC1100 Errata Notes ([swrz012.pdf](#))
- [5] CC1101 Errata Notes ([swrz020.pdf](#))
- [6] CC2500 Errata Notes ([swrz002.pdf](#))
- [7] CC1110Fx/CC1111Fx Low-Power Sub-1 GHz RF System-on-Chip (SoC) with MCU, Memory, Transceiver, and USB Controller ([cc1110f32.pdf](#))
- [8] CC2510Fx/CC2511Fx Low-Power SoC (System-on-Chip) with MCU, Memory, 2.4 GHz RF Transceiver, and USB Controller ([cc2510f32.pdf](#))

9 General Information

9.1 Document History

Revision	Date	Description/Changes
SWRA114B	2007.10.22	Removed logo from header. Added info about CC1101 and CC1111. Added info to Table 1.
SWRA114A	2007.01.12	Corrected error in code example. Added chapter 7. RSSI Threshold
SWRA114	2006.10.23	Initial release.

IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, modifications, enhancements, improvements, and other changes to its products and services at any time and to discontinue any product or service without notice. Customers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All products are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its hardware products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

TI assumes no liability for applications assistance or customer product design. Customers are responsible for their products and applications using TI components. To minimize the risks associated with customer products and applications, customers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any TI patent right, copyright, mask work right, or other TI intellectual property right relating to any combination, machine, or process in which TI products or services are used. Information published by TI regarding third-party products or services does not constitute a license from TI to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of TI information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. Reproduction of this information with alteration is an unfair and deceptive business practice. TI is not responsible or liable for such altered documentation. Information of third parties may be subject to additional restrictions.

Resale of TI products or services with statements different from or beyond the parameters stated by TI for that product or service voids all express and any implied warranties for the associated TI product or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

TI products are not authorized for use in safety-critical applications (such as life support) where a failure of the TI product would reasonably be expected to cause severe personal injury or death, unless officers of the parties have executed an agreement specifically governing such use. Buyers represent that they have all necessary expertise in the safety and regulatory ramifications of their applications, and acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of TI products in such safety-critical applications, notwithstanding any applications-related information or support that may be provided by TI. Further, Buyers must fully indemnify TI and its representatives against any damages arising out of the use of TI products in such safety-critical applications.

TI products are neither designed nor intended for use in military/aerospace applications or environments unless the TI products are specifically designated by TI as military-grade or "enhanced plastic." Only products designated by TI as military-grade meet military specifications. Buyers acknowledge and agree that any such use of TI products which TI has not designated as military-grade is solely at the Buyer's risk, and that they are solely responsible for compliance with all legal and regulatory requirements in connection with such use.

TI products are neither designed nor intended for use in automotive applications or environments unless the specific TI products are designated by TI as compliant with ISO/TS 16949 requirements. Buyers acknowledge and agree that, if they use any non-designated products in automotive applications, TI will not be responsible for any failure to meet such requirements.

Following are URLs where you can obtain information on other Texas Instruments products and application solutions:

Products		Applications	
Amplifiers	amplifier.ti.com	Audio	www.ti.com/audio
Data Converters	dataconverter.ti.com	Automotive	www.ti.com/automotive
DSP	dsp.ti.com	Broadband	www.ti.com/broadband
Interface	interface.ti.com	Digital Control	www.ti.com/digitalcontrol
Logic	logic.ti.com	Military	www.ti.com/military
Power Mgmt	power.ti.com	Optical Networking	www.ti.com/opticalnetwork
Microcontrollers	microcontroller.ti.com	Security	www.ti.com/security
RFID	www.ti-rfid.com	Telephony	www.ti.com/telephony
Low Power Wireless	www.ti.com/lpw	Video & Imaging	www.ti.com/video
		Wireless	www.ti.com/wireless

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265
Copyright © 2007, Texas Instruments Incorporated